HEAVY DUTY APPLIANCE TRUCKS



APPL-1 & APPL-2 APPLIANCE TRUCKS

STANDARD FEATURES:

- Extra height for tall loads.
- ▶ 10 ft, 2" wide retractable strap for securing loads without leaving wear marks.
- ▶ 2" wide full length wings with non-marring rubber wear strips to protect the load from surface damage.
- ▶ Double loop grip handles with 51" height assists in tipping back the load.
- ▶ 23" wide x 5" deep steel nose plate.
- Optional A1 lower handle to replace the double side loops.

APPL-1 APPLIANCE TRUCK WITH 4TH WHEEL

▶ 8" Balloon cushion wheels (D16) with deployable 4th wheel attachment to support the load when tipped back. Also includes an extended kick bar to improve leverage when tipping back a heavy load.

Height: 69". Weight: 60 lbs.

Capacity: 600 lbs. - 800 lbs. when using the 4th wheel attachment.

APPL-2 APPLIANCE TRUCK WITH SKIDS

▶ 30" skids with 10" wheels for outdoor/stair/curb applications.

Optional D5, D5S, D5G, D5F & D6 wheels.

▶ D6SS no flat 10" wheels.

Height: 69". Weight: 53 lbs.

Capacity: 600 lbs.

Liherator



HTA-8 & HTA-6 APPLIANCE TRUCKS

STANDARD FEATURES:

- ▶ 16" wide x 12" deep extruded aluminum nose plate.
- ▶ Deployable 4th wheel attachment with 8" balloon cushion wheels (D16) to support the load when tipped back.

Height: 48". Weight: 50 lbs.

Capacity: 600 lbs. - 800 lbs. when using the 4th wheel attachment

HTA-8

- ► Solid 16" deck with rubber bumper strips to protect the load.
- ► Double flared grip handle.

HTA-6 (not shown)

- ► Frame with 2" wings (no deck).
- ► Square loop handle (A37) with 55" extension.
- Optional strap to hold the load.









bpmfg.com

